

GT3000

PURSUING ULTIMATE VERSATILITY OF INSTALLATION

Genmega introduces the GT3000 series through-the-wall ATM. Designed and intended as a true through-the-wall machine, the GT3000 retains all the features and options of a retail floor model ATM in a small, compact weather resistant chassis, perfect for tight spaces Kiosks or anywhere location space is valuable.

The GT3000 uses a 7" high-resolution wide-screen LCD, 2" receipt printer and can be ordered with a fixed cassette or rear-load removable cassette dispenser. There is also an optional Rear service-panel to provide secure loading and management functions.

While the small footprint TTW chassis is all new, the GT3000 series ATM uses existing Genmega components, so service and maintenance remain easy and familiar. The GT3000 provides an economical through-the-wall solution.



GT3000



Integrated Illuminated Sign

- High Visibility LED Sign
- Attract Customers

LCD Screen

- 7 inch diagonal 32-bit color
- Backlit TFT LCD Panel
- 800 x 480 Resolution
- Customizable Ad Screens
- High bright LED Backlight (optional)

PIN Entry Device

- 16-key alphanumeric keypad
- PCI 3.0 / Interac Certified
- Triple-DES (TDES) compliant EPP

Printer

- 56mm (2" standard)

Rear Service Panel

- Optional rear service panel

Communication

- 56Kb Internal modem
- TCP/IP Ethernet connection
- SSL / TLS Encryption

CPU

- Cortex-A8 CPU
- DDR2 256MB SRAM memory
- 512MB Flash Memory
- Windows CE 6.0

ADA

- Voice Guidance
- Lighted Transaction Guidance
- Accessible Keypad Layout

Card Reader

- EMV (Dip type)

Security

- UL291 Business Hours Vault
- Electronic Lock
- Kaba Mas Cencon Series Lock (optional)
- S&G A-Series Lock (optional)

Cash Dispenser

- 800 Note Removable Cassette (TCDU)
- 2000 Note Removable Cassette (RCDU)

Dimensions

- Height = 35.5"
 - Width = 15"
 - Depth = 30"
 - Weight = 210 lbs
- * optional dispensers will increase overall weight

Power Requirements

- 110/220 VAC \pm 10%, 50/60 Hz, 86 Watts

